


LED Lighting Modules

- Excellent color uniformity for linear line bar
- High brightness modules ,
- Suitable for LED Lighting application.



Product	Color Ranks	Luminous Flux	Size mm (L x W)	Input Voltage / Current	Total Power	Recommended Drivers	Notes
LE30020-C6001-09	2700K 3000K 4000K 5000K	650 -900 lm	300 x 20	12V/1.2A	14.4W	12VDC Constant Voltage	*Connection cables are optional.




Product	Color Ranks	Luminous Flux	Size mm (L x W)	Input Voltage / Current	Total Power	Recommended Drivers	Notes
LE30422-A5001-08	2700K 3000K 4000K 5000K	600-700 lm	304 x 22	24V	9.6W	24VDC Constant Voltage	*Connection cables are optional.




Product	Color Ranks	Luminous Flux	Size mm (L x W)	Input Voltage / Current	Total Power	Recommended Drivers	Notes
LE30010-C3501-15	2700K 3000K 4000K 5000K	220-300 lm	300 x 10	12V/0.4A	4.8W	12VDC Constant Voltage	Power feed wires are optional

LED Lighting Modules


- Excellent color uniformity
- High brightness modules
- Suitable for LED lamp, LED bulbs and



Product	OA50816-C1101-04
Luminous Flux	1000-1200 lm
Size mm (d)	50
Color Ranks	2700K, 3000K, 4000K, 5000K
Input Voltage / Current	20V/700mA,1A
Total Power	14-20W
Recommended Drivers	700mA /1A Constant current



Product	OA32016-C1101-02
Luminous Flux	500-650 lm
Size mm (d)	32
Color Ranks	2700K, 3000K, 4000K, 5000K
Input Voltage / Current	20V/0.48A
Total Power	9.6W
Recommended Drivers	0.48A Constant Current




Product	OA32016-C6001-04
Luminous Flux	320-400 lm
Size mm (d)	32
Color Ranks	2700K, 3000K, 4000K, 5000K
Input Voltage / Current	12.8V/0.35A
Total Power	4.48W
Recommended Drivers	0.35A Constant Current

Intematix Technology Center


<http://www.itc-tw.com>

LED Modules

- Excellent color uniformity
- High brightness modules
- Suitable for LED downlight, table lamp



Product	OA50816-A5001-12
Luminous Flux	600-900 lm
Size mm (d)	50
Color Ranks	2700K, 3000K, 4000K, 5000K
Input Voltage / Current	19.2V/0.70A
Total Power	13.4W
Recommended Drivers	0.70A Constant Current



Product	LB06020-C6001-06
Luminous Flux	450-600 lm
Size mm (L x W)	60 x 20
Color Ranks	2700K, 3000K, 4000K, 5000K
Input Voltage / Current	24V/0.35A
Total Power	8.4W
Recommended Drivers	24VDC /400 mA

Intematix Technology Center

<http://www.itc-tw.com>